

G1900

High-Brightness Topper

Optional Topper Sign
Can accept custom inserts

Integrated Illuminated Sign

High Visibility LED Sign
Attract Customers

LCD Screen

8 inch diagonal 32-bit color
Backlit TFT LCD panel
800 x 480 Resolution
10.2 inch touch-screen Optional
8 Customizable Ad Screens

Printer

56mm Thermal Receipt Printer

PIN Entry Device

16-key alphanumeric keypad
VISA/PCI and Interac Certified
Triple-DES (TDES) compliant EPP

Communication

56,000 bps dial-up modem
TCP/IP Ethernet connection - Onboard SSL

CPU

Samsung S3C2440AL-40 RISC 32-bit CPU
64MB RAM / WinCE™ 5.0 OS
Electronic Journal > 40,000 transactions

ADA

Voice Guidance
Lighted Action Indicators
Accessible Keypad Layout

Card Reader

Dual-Head Swipe Card Reader
EMV - DIP Optional

Security

UL291 Business Hours Vault
Door Seam Reinforcement
Dial or Electronic Lock

Cash Dispenser

800 Note Fixed Cassette (TCDU)
1000 Note Removable Cassette (SCDU)
1700 Note Removable Cassette (MCDU)
2x1700 Note Multi-Cassette (MCDU)

Dimensions

Height = 56.36"
Width = 15.75"
Depth = 22.29"
Weight = 206 lbs

Power Requirements:

110/220 VAC ± 10%, 50/60 Hz, 86 Watts