

NH-2700T



System Platform

- Microsoft® Window® CE platform

Communication

- TCP/IP, Dial-up

Display

- 10" wide TFT color LCD
- **Optional** rear Supervisor panel

Input Type

- 4x2 Touch function keys
- **Optional** touch screen
- PCI compliant EPP
T-DES, DES, RSA
- **Optional** RKT

Security

- UL 291 Business hours safe
- **Optional** Level 1 safe
- Mechanical combination lock
- Electronic lock
- KABA Mas cencen lock

Card reader

- Dip type card reader
- **Optional** IC card reader
(EMV level 1,2 compliant)

Cash dispenser

- 2,000 notes cassette (Up to 3)

Printers

- Graphical thermal receipt printer

Additional Features

- Lead-through indicator
- Audio jack
- Speaker
- Illuminated topper

Power Supply

- AC 110 ~ 240V, 50 ~ 60 Hz

Environmental Conditions

- Temperature
0°C ~ 40°C (32°F ~ 104°F)
- Humidity
25% ~ 85%

Dimensions

- Height : 72 in.
- Width : 21.50 in.
- Depth : 25.24 in.
- Weight : 308.64 lbs.

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.